

# **TOP ONE TECH LIMITED**

**17" LCD Open frame SAW Touch Monitor**

**(the Water-proof and Compact Type)**

**Model: TOT170USW001**

**Part number: TOT170K1S001**



TOP ONE TECH's 17" compact open frame LCD touchmonitors have a long-lasting product cycle because the enclosure is controlled by TOP ONE TECH's specifications. Future panel improvements are therefore possible without external changes. The TOT170USW001 integrate with the TOP ONE TECH's SAW technology touchscreen.

## Features

- Bezel seal standard: NEMA3 and IEC IP65
- Long lasting product cycle-enclosure controlled by TOP ONE TECH specifications
- Future generation panels phased-in without external changes
- High quality panel with high brightness,high contrast ratio and broad viewing angle
- Multiple mounting options including VESA mount, horizontal or vertical bracket-mount
- Compact and slim profile for easy integration from side,top and bottom
- TOP ONE TECH's SAW technology on pure glass for the ultimate in image quality
- Finger or gloved hand operation
- Dual USB/Serial touch interface port
- Dual VGA/DVI input video format
- Worldwide agency approvals



## Specification

<b>Model No.</b>	<b>TOT170USW001</b>	
<b>Series</b>	OT, Water-proof and Compact	
<b>LCD Type</b>	17 " Active matrix TFT-LCD	
<b>Active Area</b>	13.3 " (338mm)×10.6 " (270mm)	
<b>Monitor Dimensions</b>	<b>Width:</b> 368mm <b>Width with brackets:</b> 389.4 mm <b>Height:</b> 306mm <b>Height with brackets:</b> 327.4mm <b>Depth:</b> 49mm for 4mm touchscreen glass	
<b>Suggested Resolution</b>	1280×1024	
<b>Support Colors</b>	16.7M	
<b>Brightness(Typ.)</b>	Pure LCD Panel	300cd/m <sup>2</sup>
	With SAW Glass Sensor	275cd/m <sup>2</sup>
<b>Response Time(Typ.)</b>	5ms	
<b>Viewing Angle (Typ.at CR&gt;10)</b>	Horizontal(left/right)	80°/80°
	Vertical(up/down)	80°/80°
<b>Contrast Ratio(Typ.)</b>	800:1	
<b>Video Input</b>	Dual Analog RGB and DVI video format	
<b>Frequency (H/V)</b>	30~80KHz / 60~75Hz	
<b>Power Supply</b>	Type: External brick Input (line) voltage: 100-240 VAC, 50-60 Hz Output voltage/current: 12 volts at 4 amps max	
<b>Environment</b>	Operating Temp.	0~50°C

	Storage Temp.	-20~60°C
	Operating RH:	20%~80%
	Storage RH:	10%~90%
<b>MTBF</b>	50,000 Hours	
<b>LCD Back light Life(Typ.)</b>	50,000 Hours	
<b>Weight (N.W/G.W)</b>	5Kg / 7.8Kg (Approx.)	
<b>Power Consumption</b>	40W Max.	
<b>Mount Interface</b>	1)VESA 75mm and 100mm 2)Mount bracket, horizontal or vertical (Standard mount brackets are supplied)	
<b>OSD Control</b>	Buttons	AUTO,+,POWER,-,MENU
	Function	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
<b>Touch screen Type</b>	TOP ONE TECH 17" SAW 4 mm compact touch sensor, anti-glare is optional	
<b>Touch System Interface</b>	Having USB and Serial(RS232) interface	
<b>Touch Response time</b>	USB/Serial: 8.4/10.4ms	
<b>Agency Approval</b>	ETL, FCC, CE, RoHS	
<b>Regular Warranty</b>	5 years for SAW Sensor; 3 years for controller; 1 year for LCD	

**NOTE: The display SPEC. will change follow the relevant LCD panel brand and model**

## Mechanical Dimensions



## Accessories

**Power Cable:** A North American power cable or an European power cable is included according to the end user's area.

**Power Supply Brick:** A power supply brick is included.

**Touch/Video/DVI Cables:** Detachable serial or USB touch cable , video cable and DVI cable are included

**L-brackets:** Four standard L-brackets are included.

## Typical Application

Gaming/Casino Systems  
Outdoor and indoor Kiosks  
Entertainment  
Transport and Ticketing  
Hospitality  
Banking  
Customized Solutions

## How to contact us

TOP ONE TECH LIMITED

Mobile Phone : (+86) 13631610695

Tel: 0086-0755-21070641

Whatsapp/Wechat : +8613631610695

Email : sales@toponetech.cn

Skype : elsieyu-sz@hotmail.com

Office in China : Room 512 & 517, Taiyangneng Guigu Building Zhongxing Xiaoqu, Yunfeng Road No.3 Gaofeng shequ, Longhua District, Shenzhen, China

Facilities in China : No. 2, Guihua Jiayi Industrial district, Guanlan, Longhua, Shenzhen, China 51804